



Toyota Landcruiser 78 series 4.5L troop carrier 2007-2014

1. Remove rear tail pipe and muffler assembly from the vehicle.
2. Remove centre connecting pipe from the vehicle.
3. Remove turbo dump catalytic converter from the vehicle. We advise to spray the 3 nuts with WD40 before removing. Hint: It is sometimes easier to locate the LHS turbo nut through the LHS wheel arch.
4. Insert the supplied EGT plug into the turbo dump pipe.
5. Fit the turbo dump pipe cat/cat delete section to the turbo outlet flange using the three supplied M10x1.25 nuts. Insert the standard gear box bracket bolt also. Tighten all 4 nuts/bolts.
6. Fit the connecting pipe to the turbo dump pipe cat/cat delete section and tighten finger tight with the supplied 3/8 UNC nuts. Also fit the rectangular mounting plate on top of the exhaust hanger mounts with the x2 10mm nuts finger tight on top.
7. Fit the over chassis connecting pipe and tighten finger tight with the supplied 3/8 UNC nuts. Also fit the rectangular mounting plates on top of the exhaust hanger mounts with the x2 10mm nuts finger tight on top.
8. Fit the pipe only/resonator or muffler section to the connecting pipe and tighten finger tight with the supplied 3/8 UNC nuts.
9. Fit the tailpipe to the pipe only/resonator or muffler section and tighten finger tight with the supplied 3/8 UNC nuts. Also fit the rectangular mounting plates on top of the exhaust hanger mounts with the x2 10mm nuts finger tight on top.
10. Check over exhaust making sure everything is aligned and then tighten all bolts and nuts from the front to back of the vehicle.
11. Enjoy your IGNITE exhaust!